
AC6815

1-1/2 inch through-bore 2 A, 3.5 A, 10 A and high speed data

Description



Typical Applications

Features

Benefts

8

8

E

B

Slip Rings With Through-Bores

| | | AC6815 Specif | cations | | 0 | ptions | | |
|---|-----------------------------------|---|--------------------------------|-----------------------|---------------|-----------------------------|-----------------------|---|
| | | | | | | | | |
| | | | | | |) | | |
| # | ₩ | | 、▋↓↓ | | | | | |
| | | |)⊪∔ | | | | | |
| | | | ───/╢┼ | | | | | |
| | *Places note that the and | erational life of the unit is dependent | | | | | | |
| | Please note that the ope | erational life of the unit is dependent | upon rotational speed environn | nent and temperature. | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | AC6815 Part N | umbering System | | | | | | |
| | | | | | F0 [| | | |
| | AC6815 | | | ┘ - 凵 凵 | 50 - | | | (|
| | | | | - / | | | | |
| | | | | AD EXITING | | | CUSTOM ODIFICATION | |
| | - | | | DE-ROTA | | ENGTH | | |
| | (| SIGNAL TY | PE | DE NOTA | | | | |
| | STATOR LEAD EXIT (STANDARD) | DEROTATION TAB THIS END ONLY (OPTIONAL) | | | | | | |
| | (STANDARD) | (OPTIONAL) | | | | El de la cala | | |
| | PI AT | | | # | of Platters | Flying Leads | | |
| | R | 244 | R#9 | | 8.0 | "L" - F 6 600 | | |
| 1 | | | | ॑ 3ऄ | | | _ | |
| | | | 5) | | | | | |
| | | | 7 | 8 – | <u>3 D</u> 08 | | DC F | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | Note: | | | | | | |
| | | Note. | | | | | | |

AC6815 Dimensions

1

